

PRIZOR VIZTECH LIMITED

PRIZ-32FHD-FL



#### **KEY FEATURES**

- HD: 1920\*1080 HIGH-DEFINITION RESOLUTION, 16: 9 GOLDEN RATIO, FINE PICTURE QUALITY, MORE COMFORTABLE VISION AND IMMERSIVE EXPERIENCE
- CLARITY: DELICATE AND LIFELIKE, CONVEYING TRUE COLORS, SHOWING TRUE COLORS
- BRIGHT: IMAGE QUALITY IS IMPROVED, ONLY FOR BETTER PRESENTATION
- ◆ THIN AND STYLISH APPEARANCE, EXQUISITE WORKMANSHIP, THE BODY IS ABOUT 8 MM THINNER, BLACK AND WHITE, ALLOWING CUSTOMERS TO HAVE MORE CHOICES
- EXCELLENT WIDE VIEWING ANGLE TECHNOLOGY ALLOWS YOU TO ENJOY HIGH-DEFINITION WONDERFUL IMAGES AND FEEL THE BEAUTY OF REAL COLORS NO MATTER FROM ANY ANGLE
- ◆ USING 8-BIT IMAGE CHIP PROCESSING TECHNOLOGY, HIGH-PIXEL PROGRESSIVE SCANNING, FINE AND LIFELIKE PICTURE QUALITY
- SUPPORT INTELLIGENT 3D NOISE REDUCTION, AFTERIMAGE ELIMINATION FUNCTION, DYNAMIC BRIGHTNESS, CONTRAST COLOR OPTIMIZATION TECHNOLOGY
- SUPPORT INTELLIGENT 3D NOISE REDUCTION, AFTERIMAGE ELIMINATION FUNCTION, CONTRAST COLOR OPTIMIZATION TECHNOLOGY
- APPLY THE WORLD'S LEADING LIQUID CRYSTAL DRIVE SCHEME TO ACCURATELY RESTORE THE FRONT-END SIGNAL, WITH A STRONG SENSE OF REALITY
- LIQUID CRYSTAL HAS SMALL SIZE, LOW ENERGY CONSUMPTION, ZERO RADIATION, STABLE IMAGE, NO IMPACT ON EYES, NATURAL AND HEALTHY
- 4MS EXTREMELY FAST RESPONSE, AVOIDING IMAGE SMEARING DURING HIGH-SPEED **OPERATION**
- USING NANOTECHNOLOGY, THE PICTURE IS MORE THREE-DIMENSIONAL AND TRANSPARENT
- NO FLICKERING + LOW BLUE LIGHT SHIELDS HARMFUL BLUE LIGHT BANDS, REDUCES INTERFERENCE FROM REFLECTED LIGHT SOURCES, AND REDUCES EYE DAMAGE

















#### PRIZ-32FHD-FL

# PRIZOR VIZTECH LIMITED

### **SPECIFICATIONS**

Model	PRIZ-32FHD-FL
Panel	
LCD Size	32 Inches
O/C	TFT Liquid Crystal Glass
Light Source	LED Backlight
Resolution	1920×1080 (Support 3840*2160 30hz)
Screen Ratio	16:9
Brightness	2 00cd/ <sup>M2</sup>
Contrast	3 000 : 1
Refresh Rate	60hz _
Reaction Time	4ms
Display Color	16.7m
Life	60,000 H(typ)
Angle Of View	H 178° /V 178°
Power Properties	
Voltage	12v/5a
Overall Power Consumption	40w
Functional Properties	
Operation Method	Panel
Working/Storage Environm	nent
Working Temperature/Humidity	0~50°C/20%~80% (No Condensation)
Storage Temperature/Humidity	-10~60°C/5%~95% ( No Condensation )









### PRIZ-32FHD-FL

## PRIZOR VIZTECH LIMITED

## **SPECIFICATIONS**

Model	PRIZ-32FHD-FL
Interface	
Input Interface	* 1, VGA*1, USB*1, Audio Output *1
Language	
OSD	Simplified Chinese, English, Etc.
Structure	
Exterior Color	Black White
Product Architecture	Metal Backlit Mixed Flame Retardant Virgin Plastic
Wall Size	100 * 100 (Mm)
Total Weight	Net Weight 4.8 Kg \ Gross Weight 6.4kg
Overall Size	713×418×40 ( Mm)
Packing Size/Single Unit	785x120x512(mm)
Packing Size/Four Sets	800x505x527(mm)
FCL Weight	26.6kg
Installation Method	Pedestal/Wall Mounted
Other	
Appendix	Bracket, Power Supply, Manual, HDMI Cable (Gift)













