



PRIZOR VIZTECH LIMITED



RP-HDV1602-5M-PRO

16CH H.265 DVR

KEY FEATURES

- ◆ 5 IN 1 HYBRID, SUPPORT HDTVI, AHD, CVI,
- ◆ SUPPORT H.265 ENCODING TECHNOLOGY, THE AVERAGE ENCODING EFFICIENCY IS INCREASED BY 50%, AND THE VIDEO STORAGE TIME IS LONGER
- ◆ ANALOG, NETWORK FIVE SIGNAL ACCESS
- ◆ THE TRANSMISSION DISTANCE OF ANALOG COAXIAL CABLE CAN REACH 600M,
- ◆ AND THE VIDEO TRANSMISSION IS RELIABLE
- ◆ SUPPORT UTC FUNCTION, DIRECTLY SET THE CAMERA THROUGH COAXIAL CABLE
- ◆ SUPPORT ONVIF PROTOCOL TO ENSURE THE INTERCONNECTION WITH THE NETWORK CAMERA
- ◆ SUPPORT MOBILE PHONE MONITORING, SUPPORT CLOUD SERVICE,
- ◆ REALIZE APP PREVIEW + REMOTE VIDEO PLAYBACK
- ◆ MOBILE APP-PRIZORPRO
- ◆ COXIAL AUDIO SUPPORTED IN TVI MODE ONLY

PRIME SERIES



SPECIFICATIONS

MODEL/NAME		RP-HDV1602-5M-PRO
VIDEO INPUT	VIDEO INPUT	16CH
	COAXIAL HD INPUT	720P/960H/1080P/4MP @15FPS/5MP@12FPS
	NETWORK VIDEO INPUT	16CH 720P/960P/1080P/3MP/4MP/5MP
	NETWORK VIDEO ACCESS BANDWIDTH	70MBPS
	AUDIO INPUT	2 CH, CAN BE EXPANDED TO 16 CH, RCA INTERFACE
AUDIO AND VIDEO OUTPUT	HDMI OUTPUT	1 CH, HDMI INTERFACE, RESOLUTION, 1920X1080P/60HZ;
	VGA OUTPUT	1 CH, VGA INTERFACE, RESOLUTION, 1920X1080P/60HZ
	AUDIO OUTPUT	RCA AUDIO OUTPUT*1, HDMI AUDIO OUTPUT
	CVBS OUTPUT	1CH, BNC INTERFACE, (OPTIONAL)
VIDEO AND AUDIO CODEC SPEC.	VIDEO COMPRESSION STANDARD	STANDARD H.265, H.264
	PLAYBACK	DVR MODE: 16-CH 720P/960H/1080P-H/3MP-H/4MP-H/5MP-H PLAYBACK; NVR MODE: 4-CH 5MP PLAYBACK;
	ANALOG VIDEO ENCODING RESOLUTION	5MP-H/(1280*1952)@6FPS;4MP-H(1280*1440)@8FPS; 1080P-H(960*1080)/720P@25FPS; 960H@25FPS
	ANALOG VIDEO CODING RATE	64 KBPS ~ 4MBPS
	STREAM TYPE	AUDIO AND VIDEO STREAMING / VIDEO STREAMING, SUPPORT VBR / CBR
	AUDIO COMPRESSION STANDARD	G.711(COAXIAL AUDIO ALSO SUPPORT)



SPECIFICATIONS

RECORDING MANAGEMENT	RECORDING MODE	TIMING , MOTION DETECTION , ALARM
	PLAYBACK MODE	REGULAR PLAYBACK
	BACKUP MODE	USB BACKUP AND NETWORK BACKUP, BACKUP BY TIME
HDD	STORAGE TYPE	SUPPORT 2 SATA INTERFACE
	STORAGE CAPACITY	EACH INTERFACE SUPPORTS A HARD DISK WITH A MAXIMUM CAPACITY OF 6TB
EXTERNAL INTERFACE	NETWORK INTERFACE	1 RJ45 100M ADAPTIVE ETHERNET PORT
	USB INTERFACE	2 USB2.0 PORTS
	ALARM INTERFACE	NA
NETWORK	NETWORK PROTOCOLS	UPNP, SNMP, NTP, SADP, SMTP, PPPOE, DHCP
OTHERS	POWER INPUT	DC 12 V & 4AMP
	POWER CONSUMPTION (WITHOUT HDD)	≤15W
	OPERATING TEMP.	-10°C--+ 55°C
	OPERATING HUMIDITY	10% --90%
	SIZE	32*25*4.8CM
	WEIGHT (WITHOUT HDD)	≤2KG

