



PRIZOR VIZTECH LIMITED

RP-POE-0802 8PORT POE SWITCH WITH 2UPLINK



KEY FEATURES

- ◆ 8PORT 10/100MBPS POE ETHERNET PORTS
- ◆ 2×10/100MBPS UPLINK PORTS(RJ45)
- ◆ ALL 100MBPS PORTS SUPPORT POE
- ◆ POE COMPLIES WITH IEEE802.3AF/AT, UP TO 30W FOR SINGLE PORT
- ◆ UP TO 250M TRANSMISSION DISTANCE ON EXTEND MODE
- ◆ EASY TO USE, NO NEED TO CONFIGURE
- ◆ HIGH QUALITY WITH ALL METAL HOUSING
- ◆ SUPPORT LIGHTING PROTECTION 6000V



**MULTIFUNCTION
SWITCH**



**LED
INDICATOR**



**LIGHTNING
PROTECTION**

1800-123-3699  www.prizor.in



SPECIFICATIONS

| | |
|------------------------|---|
| MODEL | RP-POE-0802 |
| FEATURE | SPECIFICATION |
| POWER ADAPTER VOLTAGE | AC 110V-240V |
| CONSUMPTION | 120W(52V 2.3A) |
| POE ETHERNET PORT | 1-8 PORT:10/100MBPS |
| ETHERNET PORT | UPLINK PORT:10/100MBPS |
| TRANSMISSION DISTANCE | 100MBPS:0-100M / 10MBPS:0-250M / UPLINK PORT:0-100M |
| TRANSMISSION MEDIUM | CAT5/5E/6 STANDARD NETWORK CABLE |
| NETWORK STANDARD | IEEE802.3/802.3U,IEEE802.3X,IEEE802.3AB |
| SWITCHING CAPACITY | 2GBPS |
| PACKET BUFFER MEMORY | 1MBITS |
| THROUGHPUT | 1.488MBPS |
| MAC TABLE | 1K |
| PACKET FORWARDING RATE | 10MBPS:14880PPS/PORT, 100MBPS:1488000PPS/PORT |
| POE STANDARD | IEEE802.3AF/AT |
| POE POWER SUPPLY | 1/2 +,3/6 -,8 CORE POWER SUPPLY |
| POE POWER | AF=15.4W,AT=30W FOR EACH PORT |
| PORT FUNCTION | POWER PRIORITY MECHANISM, FAST AND FORWARD, MAC AUTOMATIC LEARNING AND AGING IEEE802.3X FULL-DUPLEX AND MODE AND BACK PRESSURE FOR HALF-DUPLEX MODE |
| LED INDICATOR | LINK/ACT 100MBPS: POE STATUS INDICATOR, POWER INDICATOR, EXTENDER |
| WORKING TEMPERATURE | 0°C~50°C |
| RELATIVE HUMIDITY | 20-95% |
| STORAGE TEMPERATURE | -20°C~70°C |

