



PRIZOR VIZTECH LIMITED



PP-PEG1602-250W

16 PORT GIGA POE SWITCH

KEY FEATURES

- ◆ AI WATCHDOG FUNCTION
- ◆ AUTO-DETECT THE DATA COMMUNICATION STATUS OF ALL POE PORTS IN REAL-TIME, AND RESTART POE IP CAMERA TIMELY IF THE CAMERA IS HALTED
- ◆ AUTO-ADAPTION 250M TRANSMISSION
- ◆ USING THE LATEST TRANSMISSION TECHNOLOGY, EACH PORT OF THE SWITCH INTELLIGENTLY JUDGES THE TRANSMISSION DISTANCE AND AUTOMATICALLY ADAPTS 250M TRANSMISSION, NOT INCLUDING 1000M POE PORTS
- ◆ 6KV LIGHTNING & 8KV ESD PROTECTION
- ◆ 1000MBPS RJ45 AND SFP UPLINK PORTS



SPECIFICATIONS

| Model | |
|--------------------------------------|---|
| Network Parameters | |
| PoE Ports | 16 ×10/100 Mbps PoE ports(RJ45) |
| Uplink Ports | 2 ×10/100/1000 Mbps ports(RJ45) |
| SFP Port | 1 ×1000Mbps SFP fiber port(Data) |
| Network Standard | IEEE 802.3, IEEE 802.3u, IEEE 802.3x |
| MAC Address Table | 8K |
| Switching Capacity | 9.2Gbps |
| The Frame Filter & Transmission Rate | 14800pps the most for the long distance mode, 148800pps the most for 100M port, 1.488Mpps the most for 1000M port |
| Transmission Distance | 100Mbps /10Mbps, Auto-Adaption 250m except the last two PoE ports |
| PoE | |
| PoE Standard | IEEE 802.3af, IEEE 802.3at |
| PoE Ports | 1-16 ports |
| Power Output | PIN:1/2(+), 3/6(-) |
| Max. Port Power | 30W |
| General Parameters | |
| Power | AC 100~240V |
| Power Consumption | Max. 250W |
| Protection Level | Lightning Protection: 6KV; ESD Protection: 8KV |
| Dimensions | 440×180×45mm |
| Environment | Operating Temperature: -20°C~60°C |
| | Storage Temperature: -40°C~70°C |
| | Operating Humidity: 10%~90%Non-condensing |
| | Storage Humidity: 5%~90%Non-condensing |
| Weight (net) | < 2.8kg |
| Installation | Desktop mount; Rack mount |



DIMENSIONS

