




PRIZOR VIZTECH LIMITED



32CH NVR

PP-NVR324K-AI-DS2

KEY FEATURES

- ◆ Supports 32 CH 16MP / 12MP / 9MP / 8MP / 6MP / 5MP / 4MP / 3MP / 1080P / 1280x1024 / 960P / 720P
- ◆ High definition IP input, which adopts the advanced SOC technique to ensure
- ◆ High definition recording in each channel and realize outstanding robustness of the system.
- ◆ Supports 32CH IPC input , simultaneous 16CH playback, and 4K high definition display.
- ◆ The series of product can meet different security requirements of home, financial, commerce, enterprise, transportation and government, etc.



HD Output



HD IPC



DDNS



Network



PTZ



Audio



Mobile



CMS



USB



Mouse



E-mail



STD



VCA



1800-123-3699



www.prizor.in



SPECIFICATIONS

Model		PP-NVR324K-AI-DS2
System	OS	Embedded Linux
Video	Compression	H.265S/H.265+/H.265/H.264
	IP Video Input	32CH IPC input
	Resolution	16MP/12MP/9MP/8MP/6MP/5MP/4MP/3MP/1080P/1280i 1024/960P/ 720P/960H/D1/CIF
	Network Bandwidth	320Mbps/256Mbps (incoming/outgoing) *When the AI function of the IPC is enabled, the actual incoming bandwidth(max.bitrate) is more than the set value in the NVR.
	Output	HDMI1 : 3840 i 2160/1920 i 1080 / 1280 i 1024 / 1024 i 768 HDMI2 : 1920 i 1080 / 1280 i 1024 / 1024 i 768 VGA i 1 : 1920 i 1080 / 1280 i 1024 / 1024 i 768 VGA and HDMI1 output the same video source
	Multi-screen Display	Main output: 1/4/6/8/9/13/16/25/32/36(live view) AUX output: 1/4/6/8/9(live view) Max. 32+9CH local live view
Audio	Network Input	32 CH IPC audio input
	2-way Audio	RCA i 1
	Local Output	RCA i 1
	Compression	G.711(U/A)
Record	Resolution	16MP/12MP/9MP/8MP/6MP/5MP/4MP/3MP/1080P/1280i 1024/960P/720P/960H/D1/CIF
	Frame Rate	NTSC: 30fps; PAL: 25fps
Playback	Simultaneous Playback	Max 16CH
	Search	Time slice / time / event / tag / smart search
	Smart Search	Highlighted color to display the camera record in a certain period of time, different colors refers to different record events
	Function	Play, pause, FF, FB, digital zoom, etc.
Decoding Capability	Live View/ Playback	Non-AI Mode:1i 16MP@30fps/4i 6MP@30fps/9i 2MP@30fps/16i 720P@30fps AI Mode: 1i 16MP@30fps/4i 5MP@30fps/9i 2MP@30fps/16i 720P@30fps
Alarm	Mode	Manual, sensor, motion, exception, smart events, etc.
	Input	8 CH local alarm input
	Output	4 CH
	Triggering	Record, snap, preset, e-mail, etc.



SPECIFICATIONS

Face	Face Detection Performance (AI by IPC)	32CH
	Face Detection Performance (AI by Device)	2 CH (2MP)
	Face Match Performance	6 CH
	Comparison Capability	18 pictures / second
	Face Picture Database	32 libraries 10000 Face Pictures
	Face Picture Search	Search by picture is supported
	Database Management	Add, modify, delete and search face pictures
	Face Picture Adding	Add face pictures through APP, WEB and external import
	Face Picture Comparison	Support allow list, block list and stranger match alarm
	Track	Track display on a map
	Statistical Graph of Information	Bar graph
	Statistical Mode of Information	Statistics by day, week, month, quarter as well as customized time period

Perimeter Protection	Human/Vehicle Classification (AI by IPC)	32 CH
	Human/Vehicle Classification (AI by Device)	2CH (2MP)
Video Metadata	Human/Vehicle Attribute Analysis (AI by IPC)	Yes
Other Functions	Fisheye	Supports fisheye dewarping via NVR/Web Client/mobile APP
	Plate Recognition (AI by IPC)	Yes
Network	Interface	RJ 45 1000 Mbps $\hat{1}$ 2
	Protocol	TCP / IP, HTTP, HTTPS, 802.1X, FTP, DHCP, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, IPv6, IPv4, UDP, WebSocket, PPPoE, SNMP, IGMP
	Client Connection	Max. 128 users access
Mobile Device	OS	iOS, Andriod
Storage	HDD Interface	SATA $\hat{1}$ 2, max 10T for each HDD
Backup	Local Backup	U disk, USB mobile HDD
	Network Backup	Yes
External Interface	RS 485	Yes (full-duplex), connect to PTZ or keyboard
	USB	USB 3.0 $\hat{1}$ 1; USB 2.0 $\hat{1}$ 2
	Remote Controller	Optional
Others	Power Supply	DC12V/4A
	Consumption	\leq 20W (without HDD)
	Certificate	CE, FCC
	Environmental Protection	Complies with Directive EU RoHS, REACH and WEEE
	Dimensions(mm)	380 $\hat{1}$ 268 $\hat{1}$ 48.1 (W $\hat{1}$ D $\hat{1}$ H)
	Working Environment	-10 \sim 50 $^{\circ}$ C \sim 10% \sim 90% humidity




FEATURES

- ◆ Support 32CH 16MP/12MP/9MP/8MP/6MP/5MP/4MP/3MP/1080P/1280×1024/960P/720P/960H/D1/CIF IPC Input
- ◆ H.265S/H.265+/H.265/H.264
- ◆ Intuitive and user-friendly Graphic User Interface (GUI), Windows style operation by mouse
- ◆ Multi-type recording: manual / timed / motion / sensor / POS / AI recording
- ◆ Playback : 16 CH simultaneous playback
- ◆ Search : time slice, time, event, tag and smart search
- ◆ Support face detection and comparison
- ◆ Support multiple VCA (Video Content Analytics) events, such as object abandoned/missing, region intrusion, tripwire, video exception, etc.
- ◆ Support license plate recognition
- ◆ Support POS information overlay on live view and playback
- ◆ Pentaplex : preview, record, playback, backup and remote access DHCP, DDNS, PPPoE network protocol
- ◆ Compatible with third-party IPCs, such as ONVIF, Hikvision, etc.
- ◆ Remote control via Web Client or CMS : preview, playback, backup, PTZ and configuration
- ◆ Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device
- ◆ Multi-user online simultaneously
- ◆ Authorization management, log view and device status view 4K output, true high resolution display
- ◆ Support PTZ preset and auto cruise
- ◆ Support NAT function and QRCode scanning by mobile phones
- ◆ Powerful mobile surveillance by smart phones with iOS and Andriod OS



DIMENSIONS



REAR PANEL

TD-3004 H1-B1-B/TD-3008 H1-B1-B

