

PV-XVR1601-A1


16CH H.265

DVR




KEY FEATURES


- Support H.265/H.264 Video Formats
- Support Audio over Coaxial Cable
- Support TVI, AHO, CVI, CVBS, IP Cameras with Adaptive Access
- 16 Channel BNC Input
- Support 1ch HDMI Output, 1ch VGA Output at Up to 1920*1080
- Transmission Distance over Coax Cable
- Supports Mainstream Cameras of ONVIF and RTSP Protocols
- Mobile App- PRIZORCAM
- Coaxial Audio Supported TVI Mode




Compression
H.265




Cloud
P2P ID




Free
Online View



Audio
Input



Free Email
Alert service



Mobile
Apps



Prizor
CMS



1800-123-3699



www.prizor.in



TECHNICAL SPECIFICATION

MODEL		PV-XVR1601-A1
VIDEO/AUDIO INPUT		
IP VIDEO INPUT		2-CH(ONLY IP UP TO 18CH) EACH CHANNEL UP TO 4MP
ANALOG VIDEO INPUT		16-CH, BNC
SUPPORTED ANALOG CAMERA TYPES	SUPPORT AHD INPUT: 5MP@12.5FPS, 4MP@15FPS , 1080P@30FPS , 720P@30FPS SUPPORT TVI INPUT: 5MP@12.5FPS, 4MP@15FPS, 1080P@30FPS, 720P@30FPS SUPPORT CVI INPUT: 1080P@30FPS, 720P@30FPS , SUPPORT CVBS INPUT	
RCA AUDIO INPUT		1-CH
VIDEO/AUDIO OUTPUT		
HDMI OUTPUT		HDMI: 1920 X 1080/60 HZ, 1920 X 1080/50 HZ, 1600 X 1200/60 HZ, 1280 X 1024/60 HZ, 1280 X 720/60 HZ, 1024 X 768/60 HZ
VGA OUTPUT		VGA: 1920 X 1080/60 HZ, 1920 X 1080/50 HZ, 1600 X 1200/60 HZ, 1280 X 1024/60 HZ, 1280 X 720/60 HZ, 1024 X 768/60 HZ
RCA AUDIO OUTPUT		1-CH
LIVE VIEW DISPLAY		HDMI/VGA: 1/4/6/8/9/16/25
ENCODING/DECODING		
RECORDING RESOLUTION		5MP LITE/4MP LITE/1080P/720P/D1
RECORDING FRAME RATE		MAIN STREAM: 5MP LITE@6FPS, SUB STREAM: D1@6FPS MAIN STREAM: 4MP LITE@8FPS, SUB STREAM: D1@8FPS MAIN STREAM: 1080P@12FPS, SUB STREAM: D1@12FPS MAIN STREAM: 720P@12FPS, SUB STREAM: D1@12FPS
AUDIO SAMPLE RATE		8 KHZ, 16 BIT PER CHANNEL
AUDIO BIT RATE		64 Kbps PER CHANNEL
DECODING CAPABILITY		ANALOG: 8 X 5MP LITE@6, 8 X 4MP LITE@8, 8 X 1080P LITE @12FPS , IP: 1 X 8MP@30, 2 X 4MP@30, 4 X 1080P@30



TECHNICAL SPECIFICATION

MODEL	PV-XVR1601-A1
TWO-WAY AUDIO	1-CH, RCA (USING THE AUDIO INPUT AND OUTPUT)
ANALOG SNAPSHOT	
FTP/SCHEDULE/EVENT SNAPSHOT	FTP/EVENT SNAPSHOT:4-CH SNAPSHOT, UP TO 704*576 RESOLUTION, SCHEDULE SNAPSHOT: NOT SUPPORTED
NETWORK	
INCOMING BANDWIDTH	24MBPS (UP TO 56MBPS AFTER ALL ANALOG CHANNEL CONVERSION)
OUTGOING BANDWIDTH	64MBPS
REMOTE USERS	128
PROTOCOLS	TCP/IP, P2P, UPNP, DHCP, HTTP, HTTPS, DNS, DNS, SMTP, NTP
BROWSER(PLUGIN)	WINDOWS: IE (IE10/11), FIREFOX (VERSION 52.0 AND ABOVE), CHROME (VERSION 45 AND ABOVE), EDGE (VERSION 79 AND ABOVE)
SMART	
ANALOG SMART BY XVR	SMD
SMART FUNCTIONS BY XVR	8-CH (HUMAN & VEHICLE DETECTION)
ALARM	
GENERAL ALARM	MOTION
ALERT ALARM	IP CONFLICT, NETWORK DISCONNECTED, DISK OFFLINE, DISK ABNORMAL, ILLEGAL ACCESS, HARDDISK SPACE LOW, HARD DISK FULL, RECORDING/SNAPSHOT ABNORMAL
HARD DISK	1 SATA INTERFACE(EACH MAX 10TB)
EXTERNAL INTERFACE	
NETWORK INTERFACE	1 RJ45 10M/100M SELF-ADAPTIVE ETHERNET INTERFACE
USB	REAR PANEL: 2 X USB2.0
POWER SUPPLY	DC 12 V

